



VANADIUM PRODUCTS FOR STEEL

NITROVAN[®] VANADIUM

ALLOY	VANADIUM	NITROGEN	CARBON	ALUMINUM
Nitrovan [®] 12 Vanadium	77-81%	10-14%	10% max.	0.15% typical
Nitrovan [®] 16 Vanadium	76-81%	14-18%	6% max.	0.15% typical



Briquets: Round or oval, each approximately 1.2 in. x 1 in. x 0.8 in. (3 cm x 2.5 cm x 2 cm).

Size Range: 100% less than 3 in. (75 mm);
5% max. less than 0.25 in. (6 mm).

Major Axis of Briquet: 1.7 in. (45 mm).

Packaging: Strong, moisture-resistant bags containing 25 lbs. or 10 kg of vanadium.

FERROVANADIUM

GRADES	VANADIUM	ALUMINUM	SILICON	CARBON	PHOSPHORUS	SULFUR
Regular	75-85%	1.5% max	1.5% max	0.25% max.	.08% max.	0.08% max.
Low-Aluminum	75-85%	0.50% max.	1.5% max	0.25% max.	.08% max.	0.08% max.



Sizes: 2 in. x 18 in. mesh; 1/4 in. x 18 in. mesh.

Packaging: Bags containing 25 lbs. of vanadium in pallet boxes or shrink-wrapped on pallets.

Supersacks containing 1 metric ton or 3,000 lbs. of alloy.

Drums containing 500 lbs. of alloy.



VANOX[™] VANADIUM

VANADIUM	PHOSPHORUS
67% typical	0.03% max.

Size: Powder

Packaging: Bags containing 25 lbs. of vanadium in pallet boxes.

STRATCOR, Inc.

A Subsidiary of Strategic Minerals Corporation • Part of the Evraz Group

Omega Corporate Center

1180 Omega Drive; Pittsburgh, Pennsylvania 15205; U.S.A..

Tel.: (412) 787-4500 • Fax: (412) 787-5030

www.stratcor.com • www.evraz.com

STRATCOR is a registered trademark of Strategic Minerals Corporation.
"Nitrovan" is a registered trademark of Stratcor, Inc.

Strategic Minerals Corporation
Is Part of the Evraz Group

EVRAZ
www.evraz.com